



# Logistex MB200 Modular Belt Conveyor

## FEATURES

- Robust construction ensures longer life and heavy load handling ability
- Simple cam adjustment of snub roller and easy-to-remove pulleys
- Standard gear/motor options to meet global requirements
- Frame end covers protect internal parts and eliminate snag points
- Suitable for freezer and sub-zero applications

## BENEFITS

- Provides easy and accurate belt tracking
- Direct drives reduce parts requirements
- Increases energy efficiency
- Designed to reduce maintenance time



The new Logistex MB200 modular belt conveyor offers a wide range of economical and efficient solutions where load control and speed of operation are important. Logistex MB200 is particularly suited to transport loads of various weights and sizes, and to handle fragile product.

Logistex MB200 modular belt conveyor can be used in stand-alone applications or combined to provide an integrated solution. Available in a wide variety of modules and incline, decline and level formats, Logistex MB200 provides maximum layout flexibility to suit the requirements of individual operations.

### Module Types

- Center Drives and End Drives
- Intermediates
- End Idlers
- Jackknife units
- Upper Bends
- Manual and Pneumatic Take-up units

A cohesive family of conveyor for case, package, tote, and tray handling, Logistex Case Conveyor Solutions provide exceptional performance, superior reliability, and industry-leading throughput rates. Designed to reduce maintenance and operational costs, Logistex Case Conveyor Solutions are easy to maintain, require minimal tools and spare parts, and incorporate the latest energy-saving technologies.





# Logistex MB200 Modular Belt Conveyor



## SPECIFICATIONS

Live Load: 45 kg (100 lbs) per carton

Widths: 450 mm, 550 mm, 650 mm, 750 mm, 850 mm or 1000 mm (17.7 in, 21.6 in, 25.6 in, 29.5 in, 33.5 in or 39.4 in)

Lengths: 1 m, 2 m, 3 m or 4 m (3.28 ft, 6.56 ft, 9.84 ft or 13.12 ft)

Speeds: 12 m/min, 15 m/min, 18 m/min, 30 m/min, 45 m/min, 60 m/min, 75 m/min, 90 m/min or 120 m/min (40 ft/min, 50 ft/min, 60 ft/min, 100 ft/min, 150 ft/min, 200 ft/min, 250 ft/min, 300 ft/min or 400 ft/min)

Inclines and Declines: Available up to 30 degrees

Side Guide: Aluminum extruded construction, optional offset bracket for oversized or undersized carton requirements, optional dual extrusions for tall carton requirements, optional low and high steel channel guide



## MARKETS SERVED

- Apparel Warehousing & Distribution
- Automotive Aftermarket
- E-commerce
- Food & Beverage Distribution
- Government Post Offices
- Ground Distribution Systems
- Health & Beauty
- Mail-Order Fulfillment
- Overnight Distribution Systems
- Pharmaceuticals Distribution
- Publishing Distribution
- Retail Distribution
- Third Party Logistics

*All measurements are approximate.*

