

NESTAFLEX[®]
FLEXIBLE CONVEYORS




Gravity Skate Wheel Conveyor

Designed to expand, contract and move as required. The Nestaflex is a self-tracking, gravity skate wheel conveyor that has a per-linear-foot capacity of 226 pounds. This unit is engineered to handle multi-sized cartons in low- and medium-volume applications. The all-steel

construction provides structural integrity, whether the conveyor is fully extended or configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow and banked curves. The Nestaflex 226 is the choice for use at the retail-store level, with packaging

equipment, in low-volume shipping/receiving departments, or on assembly lines.



Skate Wheel Options



P-Black Polymer



N-Red Nylon



S-Steel

Flexible Material Handling

SMART SOLUTIONS[™]

9501 Granger Road
Cleveland, Ohio 44125

800 .669 .1501
www.flexmh.com



Nestaflex® 226 Standard Features and Options

Construction

All steel construction.

Conveyor formats

Available in 14", 18" and 24" widths. Lengths can be tailored to your needs.

Height adjustment

Standard adjustable heights from 28" to 44". Other height adjustments available.

Legs

Zinc-plated, heavy-duty leg supports are made from 1 1/8" square steel tubing and feature a welded cross member.

Side links

Conveyor side links are made from 11-gauge steel.

Skate wheel options

P) Black polymer with 7 steel ball bearings in a captive race – provides superior wheel rotation.
 N) Red nylon with nylon bushing – high-impact short conveyor runs.
 S) Steel skate wheel with steel ball bearings – impact-resistant, moderate to high volume.

Heavy-duty casters

Standard heavy-duty 5" x 1 1/2" swivel casters with steel foot brake on both ends.

Axles

Skate wheel axles are 5/16" diameter. Standard axle centers are 5 1/4", 4" and 3" to handle small cartons. Other options are available.

Couplers

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

Box stop/handle

Retractable package stop serves as an ergonomic handle.

Unidirectional side guards available for special product needs.

Optional impact section available for receiving applications.

Optional swing stick available for dockless receiving applications.

Warranty

18-month factory warranty

Specifications

14" WIDTHS		18" WIDTHS		24" WIDTHS		LENGTH ADJUSTMENT WITH 5 1/4" AXLE CENTERS		
Model 226	*Skate Wheels Per Axle	Model 226	Skate Wheels Per Axle	Model 226	**Skate Wheels Per Axle	Contracted/Extended	Leg Sets Per Unit	Bed Sections Per Unit
22614008	6	22618008	6	22624008	8	2' 4" – 8' 11"	3	2
22614012	6	22618012	6	22624012	8	3' 3" – 12' 10"	4	3
22614016	6	22618016	6	22624016	8	4' 3" – 16' 9"	5	4
22614020	6	22618020	6	22624020	8	5' 2" – 20' 9"	6	5
22614024	6	22618024	6	22624024	8	6' 2" – 24' 8"	7	6
22614028	6	22618028	6	22624028	8	7' 1" – 28' 7"	8	7
22614032	6	22618032	6	22624032	8	8' 1" – 32' 6"	9	8
22614036	6	22618036	6	22624036	8	9' 0" – 36' 5"	10	9
22614040	6	22618040	6	22624040	8	10' 0" – 40' 5"	11	10
22614044	6	22618044	6	22624044	8	10' 11" – 44' 4"	12	11
22614048	6	22618048	6	22624048	8	11' 11" – 48' 3"	13	12
22614052	6	22618052	6	22624052	8	12' 10" – 52' 3"	14	13
22614056	6	22618056	6	22624056	8	13' 10" – 56' 2"	15	14
22614060	6	22618060	6	22624060	8	14' 9" – 60' 1"	16	15

*8 skate-wheel option available on 14" wide models

**10 skate-wheel option available on 24" wide models

Call Customer Service at 800/669-1501 for more information.